

## LDR 5050 4H4 2S8P 50W L223W49R5 DC48V

PL BRICK HP | LED modules for industry and outdoor applications

### LED Street and Outdoor lighting modules with optics

These LED modules are suitable for standard compliant street lighting, paths and squares in accordance with EN 13201. These modules are designed for built-in into luminaire casings. They enable a modular luminaire design. The modules dimensions aligned with Zhaga book 15, Compatible with third party optics, e.g. from DARKOO.

### Technical data

Dimensions: 223x 49.5 mm

On-board push-in terminals (WAGO 2060)

Allowed operating temperature at tc point:

-30 to 85 °C (> 1100 mA)

Use of external LED constant-current drivers

Efficiency up to 173 lm/W

Colour rendering index Ra: > 70

Colour accuracy initially: 5 SDCM;

after 80,000 hrs. operating time: 7 SDCM

Lumen maintenance L80/B10:

80,000 hrs. (If 1100 mA)



---

### Product family benefits

- High-performance module for outdoor and street lighting
- Dimensions aligned with Zhaga book 15
- Compatible with third party optics, e.g. from LEDIL
- NTC for on-module temperature observation

## Technical data

### Electrical data

Nominal voltage	47V
Nominal current	1.1A
Type of current	DC
On-mode power	51.7W
Energy consumption in on-mode	18 kWh/1000h
Maximum forward voltage	51.6V
Max. drive current	1500 mA

### Photometrical data

Luminous efficacy	205.5 lm/W
Color rendering index Ra	≥70
Correlated color temperature CCT	4200 K
Colour consistency (McAdam ellipses)	5
Useful luminous flux (Φuse)	9601 lm

### Light technical data

Beam angle	120 °
------------	-------

### LED module information


Number of LEDs per module	12
---------------------------	----

### Specific technical data

Type	Typ.luminous flux	Typ.Colour temperature(CCT)	Colour rendering index CRI	min.] forward voltage	Max. forward voltage	Typ. Forward current	Typ.power consumption	Max. Forward current	Efficacy of the module
<b>Outdoor-Z LED-module – L72. 2W49.5H8</b>									
LDR3535	5239Lm	4200K	>70	43.47V	51.6V	500mA	21.74W	1500mA	241lm/W
	7158Lm					700mA	31.28W		228.8lm/W
	10626Lm					1100mA	51.7W		205.5lm/W

The values mentioned above represent only statistical variables on account of the complex manufacturing process of light emitting diodes. The values do not necessarily correspond exactly to the actual parameters of every single product which can vary from the typical specification. \*\* Production tolerance of voltage and power consumption: +10%/–4%; Measuring tolerance of luminous flux: ±7% \*\*\* Measuring tolerance of CRI: ±2 | CRI > 70 on request

## DIMENSIONS (All dimensions in mm)



<b>Product weight</b>	60.00 g
<b>Height EPRE</b>	6 mm
<b>Length EPREL</b>	223mm
<b>Width EPREL</b>	49.5 mm
<b>Temperatures &amp; operating conditions</b>	
<b>Performance temp. acc. to IEC 62717</b>	55 °C
<b>Maximum temperature at tc test poin</b>	95 °C
<b>Temperature range at storage</b>	-30...85 °
<b>Ambient temperature range</b>	-40...+70 °C

### Lifespan

<b>Number of switching cycles</b>	>100000
<b>Lumen maintenance factor LMF</b>	96
<b>L70B50 lifetime</b>	100000 h
<b>Additional product data</b>	
<b>Lighting technology used</b>	LED
<b>Capabilities Dimmable</b>	Yes