

LDR 3535 4H4 16S1P 50W L22W49R5DC48V

PL BRICK HP | LED modules for industry and outdoor applications

LED Street and Outdoor lighting modules with optics

lighting, paths and squares in accordance with EN 13201. These modules are designed for built-in into luminaire casings. They enable a modular luminaire design. The modules dimensions aligned with Zhaga book 15, Compatible with third party optics, e.g. from DARKOO.

Technical data

Dimensions: 223x 49.5 mm

On-board push-in terminals (WAGO 2060)

Allowed operating temperature at tc point:

-30 to 85 °C (> 1050 mA)

Use of external LED constant-current drivers

Efficiency up to 156 lm/W

Colour rendering index Ra: > 70

Colour accuracy initially: 5 SDCM;

after 50,000 hrs. operating time: 7 SDCM

Lumen maintenance L80/B10

: 50,000 hrs. (If 1050 mA)



Product family benefits

- High-performance module for outdoor and street lighting
- Dimensions aligned with Zhaga book 15
- Compatible with third party optics, e.g. from LEDIL
- NTC for on-module temperature observation

Technical data

Electrical data

Nominal voltage	48V
Nominal current	1.05A
Type of current	DC
On-mode power	50 W
Energy consumption in on-mode	18 kWh/1000h
Maximum forward voltage	49.6V
Max. drive current	1500 mA

Photometrical data

Luminous efficacy	192.4 lm/W
Color rendering index Ra	≥70
Correlated color temperature CCT	6000 K
Colour consistency (McAdam ellipses)	5
Useful luminous flux (Φuse)	9601 lm

Light technical data

Beam angle	120 °
------------	-------

LED module information


Number of LEDs per module	12
---------------------------	----

Specific technical data

Type	Typ.luminous flux	Typ.Colour temperature(CCT)	Colour rendering index CRI	min.] forward voltage	Max. forward voltage	Typ. Forward current	Typ.power consumption	Max. Forward current	Efficacy of the module
Outdoor-Z LED-module – L72. 2W49.5H8									
LDR3535	3687Lm	6000K	>70	43.2V	49.6V	350mA	15.14W	1500mA	243.5lm/W
	5103Lm					500mA	22.13W		230.6lm/W
	6849Lm					700mA	31.88W		214.9lm/W
	9601Lm					1050mA	49.9W		192.4lm/W

The values mentioned above represent only statistical variables on account of the complex manufacturing process of light emitting diodes. The values do not necessarily correspond exactly to the actual parameters of every single product which can vary from the typical specification. ** Production tolerance of voltage and power consumption: +10%/–4%; Measuring tolerance of luminous flux: ±7% *** Measuring tolerance of CRI: ±2 | CRI > 70 on request

DIMENSIONS (All dimensions in mm)



Product weight	60.00 g
Height EPRE	6 mm
Length EPREL	223mm
Width EPREL	49.5 mm
Temperatures & operating conditions	
Performance temp. acc. to IEC 62717	55 °C
Maximum temperature at tc test poin	95 °C
Temperature range at storage	-30...85 °
Ambient temperature range	-40...+70 °C

Lifespan

Number of switching cycles	>100000
Lumen maintenance factor LMF	96
L70B50 lifetime	100000 h
Additional product data	
Lighting technology used	LED
Capabilities Dimmable	Yes